



## Specification of Aluminum Based Copper-Clad Laminate


Item	Unit	Specification	Test condition
Insulation thickness	μm	Max Min	200 60
Solder resistance (288°C)	Sec.	Min	600
Thermal shock	288°C*10"/cycle	Min	6 Times
Peel strength (Normal status)	lb/in	Min	9
Breakdown Voltage	V/mil		750
Volume resistivity (Normal status >E+14)	Ω·cm		1.8x10 <sup>15</sup>
Surface resistivity (Normal status >E+12)	Ω	—	3.5x10 <sup>14</sup>
Dielectric constant			IPC-TM-650
1 MHz Normal status	—	5.6	2.5.5.3
1 GHz Normal status		5.3	2.5.5.5
Dissipation Factor			IPC-TM-650
1 MHz Normal status		0.013	2.5.5.3
1 GHz Normal status		0.010	2.5.5.5
Water absorption	%	0.2	IPC-TM-650 2.6.2.1
Thermal conductivity (measured on insulation layer only)	W/m°C	2.0	ASTM-E1461
Flammability	94V-0	Pass	IPC-TM-650 2.3.9
Tg	°C	100	IPC-TM-650 2.4.24
Td	°C	410	TBD (5wt% loss)
MOT (RTI)	°C	130	UL 746B
CTI (Comparative Tracking Index)	V	>600 (PLC=0)	UL746E DSR



## The thickness and dimension of Aluminum Based Copper-Clad Laminate

Product category	AD2 (The thickness of resin is 2~8mil)				
Dimension m/m	300~340×500~520 405/400×500~520 600~620×500~520 1200~1240×500~520 1200~1240×1020~1060				
The thickness of Single-Sided PCB with Aluminum Substrate	2.0 1/0	1.5 1/0	1.5 2/0	1.0 1/0	0.8 1/0
The thickness of Double-Sided PCB with Aluminum Substrate	2.0 1/1	1.5 H/H	1.5 1/1	1.0 1/1	0.8 1/1

- » The above thicknesses exclude the thickness of resin, and the thicknesses of copper and Aluminum can be combined arbitrarily.
- The thickness of copper foil : H oz~5.0 oz. The thickness of aluminum plate : 0.2~5.0mm.
- » Halogen free material
- » Compliance with RoHS and REACH.



## The scope of application

- » Lighting : General LED lighting.
- » Electronic devices in automobile : Ignition device, voltage regulator, auto safety control system, AC converter.
- » Power supply : Switch regulator, switch, DC-DC converter, DC-AC converter, MEGA power supply, solar power board.
- » Electronic control : Relay, transistor base, switchboard, radiator, insulating conductive board in semiconductor, motor control device.
- » Computer devices : Power supply device, soft disk driver, CPU.
- » Communication : Automobile telephone, high frequency booster mobile telephone, circuit filter, transmitting circuit.